



# TIMKEN BEARING CORP.of CANADA LTD.



3MMV9120HXVVDUMFS934 Bearing 2D drawings and 3D CAD models

3.937 Inch | 100 Millimeter x 5.906 Inch | 150 Millimeter x 1.89 Inch | 48 Millimeter TIMKEN 3MMV9120HXVVDUMFS934 Precision Ball Bearings

Bearing No. 3MMV9120HXVVDUMFS934

|                      |   |
|----------------------|---|
| Category             | Precision Ball Bearings   |
| Inventory            | 0.0   |
| Manufacturer Name    | TIMKEN  |
| Minimum Buy Quantity | N/A   |
| Weight               | 2.576   |
| Product Group        | B04270  |
| Enclosure            | 2 Seals   |
| Precision Class      | ABEC 7   ISO P4   |
| Material - Ball      | Steel   |
| Number of Bearings   | 2 (1 Pair)  |
| Contact Angle        | 25 Degree   |
| Preload              | Medium  |
| Raceway Style        | 1 Rib Inner Ring and Outer Ring                                       |
| Cage Material        | Phenolic  |
| Rolling Element      | Ball Bearing  |
| Enclosure Type       | Non Contact Seal  |
| Mounting Arrangement | Duplex-Universal  |
| Flush Ground         | Yes   |
| Inch - Metric        | Metric  |
| Other Features       | Single Row   Angular Contact   Super High Precision   High Speed Seal |
| Long Description     | 100MM Bore; 150MM Outside Diameter; 48MM                              |



## TIMKEN BEARING CORP.of CANADA LTD.

|                          |   |
|--------------------------|---|
|                          | Width; 2 Seals Enclosure; ABEC 7   ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 25 Degree Contact Angle; Phenolic Cage Material; 1 Rib Inner Rin |
| Category                 | Precision Ball Bearings   |
| UNSPSC                   | 31171531  |
| Harmonized Tariff Code   | 8482.10.50.28   |
| Noun                     | Bearing   |
| Keyword String           | Angular Contact Ball  |
| Manufacturer URL         | <a href="http://www.timken.com">http://www.timken.com</a>   |
| Manufacturer Item Number | 3MMV9120HXVVDUMFS<br>934  |
| Weight / LBS             | 5.68  |
| D                        | 5.906 Inch   150 Millimeter   |
| B                        | 1.89 Inch   48 Millimeter   |
| d                        | 3.937 Inch   100 Millimeter   |